

EVERCOAT®

INNOVATIVE SOLUTIONS
THAT PERFORM.

EZ ULTRA LITE™



**Ultra-lightweight
polyester body filler with
exceptional filling capabilities**

+

Ultra-light formula

The very latest filler technology

Ideal for large repair areas with a high build

Super easy-sanding with exceptional stock removal

Excellent adhesion on a variety of substrates

EZ ULTRA LITE is the lightest polyester body filler with exceptional build qualities and incomparable sandability. For the fast and easy filling of large repair areas – EZ ULTRA LITE is the right product.

Easy, even application of product combined with light sanding and heavy filling properties enables the quick and effective repair of large damaged areas. This quick process saves much time and money when completing larger repairs.

EZ ULTRA LITE is ideally suited for the repair of trucks and trailers as well as commercial and construction vehicles and trains.

EZ ULTRA LITE™

101342 – 3 Liter

*Test it yourself and
experience the many
advantages it brings to
your repair process!*

TECHNICAL DATA SHEET

EVERCOAT®

EZ ULTRA LITE™

Ultra-light polyester body filler with exceptional filling properties

Edition: SP04.00557 - Rev.01 | Page 1/2

DESCRIPTION AND APPLICATION	FOR PROFESSIONAL USE ONLY The ultra-light polyester body filler for the repair and filling of large repair areas. The exceptional sanding qualities and high build guarantee a fast and effective repair.
SUBSTRATES	Exceptional adhesion to a variety of suitably abraded substrates including; OE paint & clearcoat, steel, galvanised steel, zinc coated steel, aluminium, composite plastics, hard plastics, SMC, polyester filler.
PREPARATION	Before sanding, thoroughly clean the area to be repaired removing all traces of dirt, oil and wax residues. Lightly abrade the repair area to key the surface P80-P180. Use a fine abrasive to remove any deep or heavy scratch pattern P180-P220. Remove the dust. The area to be repaired must be completely dry before application of product.
MIXING	The mixing ratio is 2% by weight. Place the required amount of material on a clean, grease free, mixing board and add the requisite 2% hardener. Refer to the illustration on the product lid for an optical guide to ensuring the correct ratio. Thoroughly mix the material to a consistent, homogeneous mass that is one uniform colour. Only use the EVERCOAT hardener provided.
APPLICATION	First, apply a very thin layer of mixed material with firm pressure to the repair area. This promotes an optimum, pin-hole free application and excellent adhesion. Increase to the desired depth of repair by applying layers of product.
FINISHING	Sand and shape the body filler with P80 – P180 grit, avoiding deep sand scratches outside of the repair area. Finish the repair area with P180 - P220 grit. For an optimal result; apply a top layer of stopper such as EVERCOAT Easy Sand (#101669). This will guarantee a flat, pin-hole free finish and will reduce the consumption of primer in the next stages of the repair process.
TECHNICAL DATA	Colour Light grey
	Physical State Liquid
	Solubility Not soluble in cold and warm water
	Working time 3-5 minutes
	Dry to sand time 15-20 minutes
	Corrosion Protection 500 hours salt spray (Harshaw)
	Maximum build 6 -10 mm (sanded)
	Ingredients and Precautions Safety data sheet (MSDS) available on request
	VOC EU limit for volatile organic compounds: 250 g/l (2007) This product contains max 160 g/l VOC
The properties are typical values and not to be considered as technical sales specifications. The physical test was at about 25 °C and 75 % relative humidity unless otherwise specified.	
STABILITY	Best before date: 18 month from manufacturing date The manufacturing date is within the batch-identification number on the bottom of the can or on the label. The batch-identification is composed as follow: 24 10 001320 24 = year 2024 10 = month October 001320 = running batch number
STORAGE	According to the requirements of local regulations. Observe the precautionary statements given on the label. Maximum storage temperature 25 ° C. Store in a cool, well-ventilated place away from incompatible materials and sources of ignition. Keep away from oxidising agents, strong alkalis and acids. Smoking is prohibited in the immediate vicinity. Prevent unauthorized access. Opened containers should be closed ca-refully and tightly. Keep upright to prevent leakage. Do not empty into drains. Do not return mixed material to the original container.
SAFETY INSTRUCTIONS	Be sure to read all instructions and warnings before using EVERCOAT products. Safety data sheets for all materials are available online at https://itwevercoat-sds.thewerco.com/ .

EVERCOAT®



INDASA

Official distributor
partner for Europe

Your EVERCOAT partner:

INDASA - INDÚSTRIA DE ABRASIVOS, S.A.

Apartado 3005
3801-101 Aveiro, Portugal
Tel. +(351) 234 303 600
Fax +(351) 234 303 605
E-mail: indasa@indasa.pt