

## 440 EXPRESS™



### Pre-Primer Surfacer with High Quality Resin



- +**
- Optimum surface preparation**
- Patented 1K Polyester technology**
- Insulates the surface and avoids primer abuse**
- Reduces primer consumption by approx. 30%**
- Reliable filling of pin-holes and fine sanding marks**
- Avoidance of repair markings**
- Prevents painting defects due to primer abuse**



Micro-porosities are nearly invisible and often lead to painting defects



After the application of 440 EXPRESS the pores are visible and reliably sealed.

440 EXPRESS is a patented 1k pre-prime surfacer produced with a highly effective premium resin and the latest in micro sphere technology.

In just 30 seconds you can improve your process with the significant reduction of micro-porosity in the repair which is the root cause of many paint problems. Apply 440 EXPRESS pre-primer surfacer in a thin application over the repair area as your very last step before the application of the foundation coating. The 1k premium resin acts like a protective layer isolating the repair area before painting. Difficult to see micro-pores and surface sand scratches are completely filled and the surface layer sealed. After application no sanding or cleaning is necessary before painting. The sealing and isolating of the repair area significantly improves the effectiveness of the primer - saving at least one coat. This also reduces the instances of mapping and solvent entrapment. This simple step in the process eliminates 90% of the causes of re-work and guarantees a optimized, consistent, high standard of repair. 440 EXPRESS is also ideal for the preparation of plastic parts such as bumpers prior to priming.

- 440 EXPRESS™**
- # 104415 – 118 ml
- # 104400 – 473 ml
- # 104439 – Application Sponge with pad

*Test it yourself and  
experience the many  
advantages it brings to  
your repair process!*

# TECHNICAL DATA SHEET

# EVERCOAT®

## 440 EXPRESS™

Pre-Primer Surfer with High Quality Resin

Edition: SP04.00555 - Rev.01 | Page 1/2

<b>DESCRIPTION AND APPLICATION</b>	<b>FOR PROFESSIONAL USE ONLY</b> 440 EXPRESS is a 1K pre-primer surfer made with premium resin for the elimination of micro pores and surface sand scratches. It is an ideal preparation of the repair surface before the next stage of the process. Simply apply a thin, even layer of 440 EXPRESS as the very last stage before priming.
<b>SUBSTRATES</b>	Exceptional adhesion to a variety of suitably abraded substrates including; OE paint & clear coat, steel, hard plastics, composite plastics, hard plastics, SMC, polyester filler.
<b>PREPARATION</b>	Abrade the repair area with P180 grit or finer. Remove any dust with compressed air.
<b>MIXING</b>	Shake thoroughly before use to ensure the premium resin and micro-spheres are well mixed.
<b>APPLICATION</b>	Dispense a small amount of 440 EXPRESS (teaspoon) onto an application sponge (104439) or a clean, lint-free, paper towel and rub the material firmly over the entire repair area with a circular motion. By larger repair areas or where pin-holes are identified, a second application is advised. Wipe away any excess material with a clean paper towel. The remaining material should be thin and even. TIP: If there is too much material remaining, allow 15 minutes to dry and lightly remove with P180 or P320 abrasive.
<b>FINISHING</b>	After a drying time of 15 minutes the area can be over-painted with the primer, following the paint manufacturer's recommended process. No sanding or cleaning is required prior to painting.
<b>TECHNICAL DATA</b>	<b>Colour</b> Grey
	<b>Physical State</b> Liquid
	<b>Solubility</b> Not soluble in cold and warm water
	<b>Drying time</b> 15 minutes
	<b>Ingredients and Precautions</b> Safety data sheet (MSDS) available on request
	<b>VOC</b> EU limit for volatile organic compounds: 250 g/l (2007) This product contains max 151g/l VOC
	The properties are typical values and not to be considered as technical sales specifications. The physical test was at about 25 °C and 75 % relative humidity unless otherwise specified.
<b>STABILITY</b>	<b>Best before date: 12 month from manufacturing date</b> The manufacturing date is within the batch-identification number on the bottom of the can or on the label. The batch-identification is composed as follow: 24 10 001320 24 = year 2024   10 = month October   001320 = running batch number
<b>STORAGE</b>	According to the requirements of local regulations. Observe the precautionary statements given on the label. Maximum storage temperature 25 ° C. Store in a cool, well-ventilated place away from incompatible materials and sources of ignition. Keep away from oxidising agents, strong alkalis and acids. Smoking is prohibited in the immediate vicinity. Prevent unauthorized access. Opened containers should be closed carefully and tightly. Keep upright to prevent leakage. Do not empty into drains. Do not return mixed material to the original container.
<b>SAFETY INSTRUCTIONS</b>	Be sure to read all instructions and warnings before using EVERCOAT products. Safety data sheets for all materials are available online at <a href="https://itwevercoat-sds.thewerco.com/">https://itwevercoat-sds.thewerco.com/</a> .

# EVERCOAT®



Official distributor  
partner for Europe

## INDASA - INDÚSTRIA DE ABRASIVOS, S.A.

Apartado 3005  
3801-101 Aveiro, Portugal  
Tel. +(351) 234 303 600  
Fax +(351) 234 303 605  
E-mail: [indasa@indasa.pt](mailto:indasa@indasa.pt)

Your EVERCOAT partner:

