

# EVERCOAT®

INNOVATIVE SOLUTIONS  
THAT PERFORM.

## ***EZ LITE COMMERCIAL***



**Deep filling light  
weight body filler**



**Extended work time**

**Deep filling light weight body filler**

**Exceptional vertical hold**

**Smooth application**

**Superior adhesion**

**Micro-Weight™ Light weight formula**

Smooth application and easy sanding light weight body filler. EVERCOAT EZ LITE COMMERCIAL is specially formulated to allow for a deep filling with excellent vertical hang.

**EZ LITE COMMERCIAL**

# 101360 – 3 Liter

***Test it yourself and  
experience the many  
advantages it brings to  
your repair process!***

# TECHNICAL DATA SHEET

**EVERCOAT®**

## EZ LITE COMMERCIAL

Deep filling light weight body filler

Edition: SP04.00566 - Rev.01 | Page 1/2

<b>DESCRIPTION AND APPLICATION</b>	EVERCOAT EZ LITE COMMERCIAL is specially formulated to allow for a deep filling with excellent vertical hang. Operators can mix and spread large quantities with confidence knowing they have enough time to work larger surfaces. This reduces the number of mixes, saving time and increasing productivity.	
<b>SUBSTRATES</b>	Steel, and other zinc coated steel, aluminum, fiberglass, and SMC.	
<b>PREPARATION</b>	Clean surface. Remove all dirt, oil grease and wax. Use P80-P180 grit abrasives to remove and sand paint. Thoroughly clean surface using a suitable surface cleaner such as a solvent or waterbased panel preparation solution. Surface must be completely dry before application.	
<b>MIXING</b>	Use with EVERCOAT Cream Hardener Only! Place desired amount of putty on a clean, non-fibrous/non-porous mixing board. Add hardener in a ratio of 100 parts EVERCOAT EZ LITE COMMERCIAL to 2 parts. EVERCOAT CREAM HARDENER by weight. EXAMPLE: For a 5 cm diameter puddle of filler add a bead of cream hardener from the centre to the edge of the puddle. For a 10 cm diameter puddle add a bead of hardener from edge to edge. Puddles larger than 10 cm in diameter will require additional hardener. Mix thoroughly until a uniform colour is achieved.	
<b>APPLICATION</b>	Spread a thin layer of mixed materials over surface using firm pressure to ensure best adhesion. Apply additional layers building area slightly higher than the surface to allow for sanding.	
<b>FINISHING</b>	Sand and shape the body filler with P80 – P220 grit abrasive. Avoid coarse sand scratches outside of the filler area during the initial cut. Finish sand body filler with P180-P220 grit. For best results over-coat with EVERCOAT OPTEX SUPERBUILD 4:1 Polyester Primer Surfacer with built in guide coat.	
<b>TECHNICAL DATA</b>	<b>Colour</b>	Grey
	<b>Physical State</b>	Paste
	<b>Solubility</b>	Not soluble in cold and warm water
	<b>Working time</b>	7 - 9 minutes
	<b>Dry to sand time</b>	25 - 30 minutes
	<b>Corrosion Protection</b>	500 hours salt spray (Harshaw)
	<b>Maximum build</b>	6.3 mm (sanded)
	<b>Ingredients and Precautions</b>	Safety data sheet (MSDS) available on request
	<b>VOC</b>	Refer to Section 9 of the Safety Data Sheet
	The properties are typical values and not to be considered as technical sales specifications. The physical test was at about 22 °C and 75 % relative humidity unless otherwise specified.	
<b>STABILITY</b>	<b>Best before date: 18 month from manufacturing date.</b> The manufacturing date is within the batch-identification number on the bottom of the can or on the label. The batch-identification is composed as follow: 8 10 233 8 = year 2018   10 = month Octobre   233 = running batch number	
<b>STORAGE</b>	According to the requirements of local regulations. Observe the precautionary statements given on the label. Maximum storage temperature 25 ° C. Store in a cool, well-ventilated place away from incompatible materials and sources of ignition. Keep away from oxidising agents, strong alkalis and acids. Smoking is prohibited in the immediate vicinity. Prevent unauthorized access. Opened containers should be closed carefully and tightly. Keep upright to prevent leakage. Do not empty into drains. Do not return mixed material to the original container.	
<b>SAFETY INSTRUCTIONS</b>	Be sure to read all instructions and warnings before using EVERCOAT products. Safety data sheets for all materials are available online at <a href="https://itwevercoat-sds.thewerco.com/">https://itwevercoat-sds.thewerco.com/</a> .	

**EVERCOAT®**Official distributor  
partner for Europe

Your EVERCOAT partner:

**INDASA - INDÚSTRIA DE ABRASIVOS, S.A.**Apartado 3005  
3801-101 Aveiro, Portugal  
Tel. +(351) 234 303 600  
Fax +(351) 234 303 605  
E-mail: [indasa@indasa.pt](mailto:indasa@indasa.pt)