

## MASKING TAPES

# MAXIMUM PERFORMANCE GUARANTEED



### MTE-RED WP - 212° F

Adhesive	Natural rubber
Thickness	5.4 mil
Temperature	212 / 30 min
Tensile Strength	22 lb / in
Adhesion to Steel	26 oz / in



### MTE-YELLOW - 230° F

Adhesive	Natural rubber
Thickness	5.7 mil
Temperature	230 / 60 min
Tensile Strength	28 lb / in
Adhesion to Steel	27 oz / in



### MTE-GREEN - 250° F

Adhesive	Natural rubber
Thickness	5.9 mil
Temperature	250 / 60 min
Tensile Strength	29 lb / in
Adhesion to Steel	29 oz / in

# MASKING SOLUTIONS

## MTE RED WP



- Waterproof
- Solvent resistant
- UV Resistant
- Excellent adhesion
- Easy / clean removal
- Performance grade quality and thickness

## MTE GREEN



- Waterproof
- Solvent resistant
- UV Resistant
- Excellent adhesion
- Easy / clean removal
- Performance grade quality and thickness

## MTE YELLOW




- Waterproof
- Solvent Resistant
- Excellent adhesion
- Easy / clean removal
- Performance grade quality and thickness

## Fine Line Tape [BLUE]



- Flexible
- Extremely flat PVC Backing
- Easy / clean removal
- 270° F temp rating
- Excellent conformability for curves / contours

## Trim Masking Tape



- Quick & easy way to mask and protect windscreen rubber / trim
- Extremely flexible plastic film
- Perforated for easy tear and application
- Eliminates the risk of overspray & paint build up

## Masking Foam



- Flexible
- Easy / clean removal
- Solvent resistant
- Easy roll release
- 176° F temp rating
- Cylindrical profile
- Box dispenser

## Cover Rolls



- Excellent adhesion
- Easy / clean removal
- Solvent resistant
- Easy roll release
- Static cling

High performance in  
**adhesive fixing and masking solutions.**

